

# Showcase Lighting Options



## T8 Fluorescent SlimLite Light Strip

- Initial lumen output of up to 2950.
- Average life span of 20,000 hours.
- Self contained system includes an electronic ballast.
- Lamp is 1" in diameter.
- Available in 34", 46", 58", and 68" lengths.
- Standard light shield colors are clear, black, and gold anodized. Mounting clips included.



## Halogen Light Strip

- Self contained system includes a 150 watt, 12 volt transformer.
- Accepts up to (6) 20-watt bi-pin halogen lamps.
- Available in 34", 46", 58", and 68" lengths.
- Standard light shield colors are clear, black, and gold anodized. Mounting clips included.



## T5 High Output Fluorescent Light Strip

- High initial lumen output of up to 5000.
- Average life span of 30,000 hours.
- Self contained electronic ballast.
- Lamp is 5/8" in diameter.
- Available in 34", 46", 58", and 68" lengths.
- Standard light shield colors are clear, black, and gold anodized. Mounting clips included.

## MR11 Halogen Light Track

- Slim-Line track accepts clip-on light fixtures that are adjustable at most angles.
- Each transformer will power up to (7) 20-watt light fixtures.
- 150 watt, 12 volt transformer.
- Bulbs have an average life span of 1,500 hours.
- High bond tape backing for vertical installation.
- Available in 36", 48", and 60" lengths.



## Halogen Par Light for Top Crown

- Can Light is 3 - 5/16" in diameter and 3" high.
- Flange at open end.
- 50 watt PAR-20 halogen bulb.
- Screw-in type lamp.

## Additional Lighting Options

- UL Approval
- Case to Case Wiring
- Case to Case Wiring with UL Approval
- On/Off Light Switch
- Jumper Cord